



TECHNICAL SPECIFICATIONS								
Max working negative pressure						Pa	15000	
Working temperature						°C	-10<T<60	
Electric control panel feeding						230 V AC 50Hz		
Bag cleaning system						pulse-set		
Compressed air tank working pressure						bar	5	
DIMENSIONS								
Model	Filtering surface	Number of filtering elements	Number of cleaning valves	Compressed air consumption	A	H Tot	Ø In	Ø Out
	[m ²]	[-]	[-]	[NL/activ]	[mm]	[mm]	[mm]	[mm]
CNSB19-10	7	19	5	87	1000	3000	120	180
CNSB19-15	11	19	5	87	1000	3500	180	220
CNSB19-20	15	19	5	87	1000	4000	200	250
CNSB19-25	19	19	5	87	1000	4500	220	280
CNSB32-10	12	32	6	87	1300	3100	180	220
CNSB32-15	19	32	6	87	1300	3600	200	250
CNSB32-20	25	32	6	87	1300	4100	250	315
CNSB32-25	32	32	6	87	1300	4600	280	380
CNSB55-10	21	55	9	87	1600	3300	220	300
CNSB55-15	32	55	9	87	1600	3800	280	380
CNSB55-20	43	55	9	87	1600	4300	315	420
CNSB55-25	54	55	9	87	1600	4800	380	400x450
CNSB84-10	32	84	10	87	1900	3550	280	380
CNSB84-15	49	84	10	87	1900	4050	350	400x400
CNSB84-20	65	84	10	87	1900	4550	400	400x550
CNSB84-25	83	84	10	87	1900	5050	450	400x700